

Official Journal

of the European Communities

ISSN 0378-6978

L 52

Volume 39

1 March 1996

English edition

Legislation

Contents

Joint actions adopted by the Council of the European Union

96/173/CFSP:

- ★ Council Decision of 16 February 1996 amending Decision 94/942/CFSP on the joint action adopted by the Council on the basis of Article J.3 of the Treaty on European Union concerning the control of exports of dual-use goods 1

Corrigenda

- ★ Corrigendum to Council Regulation (EC) No 3381/94 of 19 December 1994 setting up a Community regime for the control of exports of dual-use goods (OJ No L 367 of 31. 12. 1994) 17
- ★ Corrigendum to Council Decision 94/942/CFSP of 19 December 1994 on the joint action adopted by the Council on the basis of Article J.3 of the Treaty on European Union concerning the control of exports of dual-use goods (OJ No L 367 of 31. 12. 1994) 18
- ★ Corrigendum to Council Decision 95/127/CFSP of 10 April 1995 amending Decision 94/942/CFSP on the joint action adopted by the Council on the basis of Article J.3 of the Treaty on European Union concerning the control of exports of dual-use goods (OJ No L 90 of 21. 4. 1995) 24

(Joint actions adopted by the Council of the European Union)

COUNCIL DECISION

of 16 February 1996

amending Decision 94/942/CFSP on the joint action adopted by the Council on the basis of Article J.3 of the Treaty on European Union concerning the control of exports of dual-use goods

(96/173/CFSP)

THE COUNCIL OF THE EUROPEAN UNION,

Article 2

Having regard to the Treaty on European Union, and in particular Article J.3 thereof,

Having regard to the general guidelines given by the European Council on 26 and 27 June 1992,

Having regard to Council Decision 94/942/CFSP of 19 December 1994 on the joint action adopted by the Council on the basis of Article J.3 of the Treaty on European Union concerning the control of exports of dual-use goods⁽¹⁾,

Whereas the lists of goods in Annex I and Annex IV to Decision 94/942/CFSP should be updated,

The list in Annex IV to Decision 94/942/CFSP, referred to in Article 5 of that Decision and in Article 19 (1) (b) of Regulation (EC) No 3381/94, shall be amended in accordance with Annex II hereto.

Article 3

This Decision shall be published in the *Official Journal*.

It shall enter into force on the day of its publication.

This Decision shall apply from 1 April 1996.

HAS DECIDED AS FOLLOWS:

Article 1

Done at Brussels, 16 February 1996

The list of dual-use goods in Annex I to Decision 94/942/CFSP, referred to in Article 2 of that Decision and in Article 3 (1) of Regulation (EC) No 3381/94⁽²⁾, shall be amended in accordance with Annex I hereto.

For the Council
The President
S. AGNELLI

⁽¹⁾ OJ No L 367, 31. 12. 1994, p. 8. Decision as amended by Decision 95/127/CFSP (OJ No L 90, 21. 4. 1995, p. 2) and Decision 95/128/CFSP (OJ No L 90, 21. 4. 1995, p. 3).

⁽²⁾ Council Regulation (EC) No 3381/94 of 19 December 1994 setting up a Community regime for the control of exports of dual-use goods (OJ No L 367, 31. 12. 1994, p. 1). Regulation as amended by Regulation (EC) No 837/95 (OJ No L 90, 21. 4. 1995, p. 1).

ANNEX I

Annex I to Decision 94/942/CFSP shall be amended as follows:

1. DEFINITION OF TERMS

- 1.1. DEF 26 “Composite theoretical performance” (CTP) (4). . .’ should be “Composite theoretical performance” (CTP) (3 4). . .’.
- 1.2. DEF 45 “Electronic assembly” (3 4). . .’ should be “Electronic assembly” (3 4 5). . .’.
- 1.3. DEF 49 “Expert systems” (4). . .’ should be “Expert systems” (4 7). . .’.
- 1.4. DEF 53 For this definition, substitute the following:

“Fibrous or filamentary materials” (0 1 8) include:

 - a. continuous “monofilaments”;
 - b. continuous “yarns” and “rovings”;
 - c. “tapes”, fabrics, random mats and braids;
 - d. chopped fibres, staple fibres and coherent fibre blankets;
 - e. whiskers, either monocrystalline or polycrystalline, of any length;
 - f. aromatic polyamide pulp.’
- 1.5. DEF 191 “Isolated live cultures”. . .’ should be “Isolated live cultures” (1). . .’.
- 1.6. Between definitions 97 and 98, insert the following:

‘193. “Monofilament” (1) or filament is the smallest increment of fibre, usually several micrometres in diameter.’
- 1.7. Between definitions 121 and 122, insert the following:

‘194. “Pressure transducers” (2) are devices that convert pressure measurements into an electrical signal.’
- 1.8. Between definitions 140 and 141, insert the following:

‘195. “Roving” (1) is a bundle (typically 12 to 120) of approximately parallel “strands”.

NB: “Strand” is a bundle of “monofilaments” (typically over 200) arranged approximately parallel.’
- 1.9. Between definitions 171 and 172, insert the following:

‘196. “Tape” (1) is a material constructed of interlaced or unidirectional “monofilaments”, “strands”, “rovings”, “tows”, or “yarns”, etc., usually preimpregnated with resin.

NB: “Strand” is a bundle of “monofilaments” (typically over 200) arranged approximately parallel.’
- 1.10. Between definitions 178 and 179, insert the following:

‘197. “Tow” (1) is a bundle of “monofilaments”, usually approximately parallel.’

- 1.11. After the last definition 185, insert the following:

'198. "Yarn" (1) is a bundle of twisted "strands".

NB: "Strand" is a bundle of "monofilaments" (typically over 200) arranged approximately parallel.'

2. CATEGORY 0

- 2.1. 0A002 Note: 'This entry...' should be '0A002...'.

- 2.2. 0B001.c.6 For this sub-entry, substitute the following:

'6. rings or bellows with a wall thickness of 3 mm or less and a diameter of between 75 and 400 mm and designed to give local support to a rotor tube or to join a number together, made from any of the following high strength-to-density ratio materials:

- a. maraging steel capable of an ultimate tensile strength of 2 050 MPa or more;
- b. aluminium alloys capable of an ultimate tensile strength of 460 MPa or more; or
- c. "fibrous or filamentary materials" with a "specific modulus" of more than $3,18 \times 10^6$ m and a "specific tensile strength" greater than $76,2 \times 10^3$ m;.

- 2.3. 0B001.c.7. For this sub-entry, substitute the following:

'7. baffles of between 75 and 400 mm diameter for mounting inside a rotor tube, made from any of the following high strength-to-density ratio materials:

- a. maraging steel capable of an ultimate tensile strength of 2 050 MPa or more;
- b. aluminium alloys capable of an ultimate tensile strength of 460 MPa or more; or
- c. "fibrous or filamentary materials" with a "specific modulus" of more than $3,18 \times 10^6$ m and a "specific tensile strength" greater than $76,2 \times 10^3$ m;.

- 2.4. 0B001.c.8.c. '... $7,62 \times 10^4$...' should be '... $76,2 \times 10^3$...'.

- 2.5. 0B001.g.5. 'Lasers or laser systems...' should be "Lasers" or "laser" systems...'.

- 2.6. 0B001.g.5 Insert on a new line after '...time;' the following text:

'NB: See also 6A005 and 6A205.'

- 2.7. 'Lasers or laser systems...' should be "Lasers" or "laser" systems...'.

- 2.8. 0B001.h.6 Insert on a new line after 'time;' the following text:

'NB: See also 6A005 and 6A205.'

- 2.9. 0B001.k Sub-entry reference 'k.' should be 'j.'.

- 2.10. 0B001.j.2 '... [non-magnetic??] ...' should be '... non-magnetic ...'.

- 2.11. 0B001.j.5 Insert on a new line at the end of the sub-entry, the following text:

'NB: See also 3A227.'

- 2.12. 0B001.j.6 Insert on a new line at the end of the sub-entry, the following text:

'NB: See also 3A226.'

- 2.13. 0B007 For this entry, substitute the following:
'Not used'.
- 2.14. 0C006 For this entry, substitute the following:
'0C006 Nickel powder or porous nickel metal, specially prepared for the manufacture of gaseous diffusion barriers, as follows:
NB: See also 1C240.
a. powder with a nickel purity content of 99,9 weight percent or more and mean particle size of less than 10 micrometres measured by American Society for Testing and Materials (ASTM) B330 standard and a high degree of particle size uniformity; or
b. porous nickel metal produced from materials specified in 0C006.a.'

3. CATEGORY 1

- 3.1. 1A202 Composite structures, other than those specified in 1A202, in the form of tubes with an inside diameter of between 75 mm and 400 mm made with any of the 'fibrous or filamentary materials' specified in 1C010.a. or b. or 1C210.a. or with carbon prepreg materials specified in 1C210.c.
NB: See also 9A010 and 9A110.'
- 3.2. 1A226 For this entry, substitute the following:
'1A226 Specialized packings for use in separating heavy water from ordinary water and made of phosphor bronze mesh (chemically treated to improve wettability) and designed for use in vacuum distillation towers.'
- 3.3. 1A227 For this entry, substitute the following:
'1A227 High-density (lead glass or other) radiation shielding windows greater than 0,09 m² on cold area and with a density greater than 3 g/cm³ and a thickness of 100 mm or greater; and specially designed frames therefor.'
- 3.4. 1B101 Note: '... this entry ...' should be '... 1B101 ...'.
- 3.5. 1B101.d Note: '... by this subheading ...' should be '... in 1B101.d ...'.
- 3.6. 1B115 Note 1: '... this item ...' should be '... 1B115 ...'.
- 3.7. 1B228 For this entry, substitute the following:
'1B228 Hydrogen-cryogenic distillation columns having all of the following characteristics:
a. designed to operate with internal temperatures of 35 K (-238°C) or less;
b. designed to operate at an internal pressure of 0,5 to 5 MPa (5 to 50 atmospheres);
c. constructed of "fine-grain stainless steels" of the 300 series with low sulphur content or equivalent cryogenic and H₂-compatible materials; and
d. with internal diameters of 1 m or greater and effective lengths of 5 m or greater.
Technical note:
"Fine-grain stainless steels" in 1B228 are defined as fine-grain austenitic stainless steel with an ASTM (or equivalent standard) grain size number of 5 or greater.'

- 3.8. 1B229 For this entry, substitute the following:

'1B229 Water-hydrogen sulphide exchange tray columns constructed from "fine carbon steel" with a diameter of 1,8 m or greater, which can operate at nominal pressures of 2 MPa or greater, and internal contactors therefor.

Notes: 1. For columns which are specially designed or prepared for the production of heavy water see 0B004.

2. Internal contactors of the columns are segmented trays which have an effective assembled diameter of 1,8 m or greater, are designed to facilitate countercurrent contacting and are constructed of materials resistant to corrosion by hydrogen sulphide/water mixtures. These may be sieve trays, valve trays, bubble cap trays, or turbogrid trays.

3. "Fine carbon steel" in 1B229 is defined as steel with the austenitic ASTM (or equivalent standard) grain size number of 5 or greater.

4. Materials resistant to corrosion by hydrogen sulphide/water mixtures in 1B229 are defined as stainless steels with a carbon content of 0,03 % or less.'

- 3.9. 1B231 For this entry, substitute the following:

'1B231 Tritium facilities, plant or equipment, as follows:

- a. facilities or plant for the production, recovery, extraction, concentration, or handling of tritium;
- b. equipment for tritium facilities or plant, as follows:
 1. hydrogen or helium refrigeration units capable of cooling to 23 K (-250°C) or less, with heat removal capacity greater than 150 watts; or
 2. hydrogen isotope storage and purification systems using metal hydrides as the storage, or purification medium.'

- 3.10. 1B232 and 1B233 After entry 1B231, insert the following two new entries:

'1B232 Turboexpanders or turboexpander-compressor sets designed for operation below 35 K (-238°C) and a throughput of hydrogen gas of 1 000 kg/hr or greater.

1B233 Lithium isotope separation facilities, plant or equipment, as follows:

- a. facilities or plant for the separation of lithium isotopes;
- b. equipment for the separation of lithium isotopes, as follows:
 1. packed liquid-liquid exchange columns specially designed for lithium amalgams;
 2. mercury and/or lithium amalgam pumps;
 3. lithium amalgam electrolysis cells;
 4. evaporators for concentrated lithium hydroxide solution.'

- 3.11. 1C115c For this sub-entry, substitute the following:

'c. other propellant additives and agents:

1. butacene;
2. triethylene glycol dinitrate (TEGDN);
3. 2-nitrodiphenylamine;
4. trimethylolethane trinitrate (TMETN);
5. diethylene glycol dinitrate (DEGDN).'

- 3.12. 1C115 *Note: "...specified here..." should be "...specified in 1C115..."*

3.13. 1C202 For this entry, substitute the following:

‘1C202 Alloys, other than those specified in 1C002.a.2.c or d, as follows:

- a. aluminium alloys capable of an ultimate tensile strength of 460 MPa or more at 293 K (20°C), in the form of tubes or cylindrical solid forms (including forgings) with an outside diameter of more than 75 mm;
- b. titanium alloys capable of an ultimate tensile strength of 900 MPa or more at 293 K (20°C) in the form of tubes or cylindrical solid forms (including forgings) with an outside diameter of more than 75 mm.

Technical note:

The phrase “alloys capable of” encompasses alloys before or after treatment.’

3.14. 1C210 For this entry, substitute the following:

‘1C210 “Fibrous or filamentary materials” or prepregs, other than those specified in 1C010.a or b, as follows:

- a. carbon or aramid “fibrous or filamentary materials” having a “specific modulus” of $12,7 \times 10^6$ m or greater or a “specific tensile strength” of 235×10^3 m or greater;

except:

aramid “fibrous or filamentary materials” having 0,25 % or more by weight of an ester based fibre surface modifier;

- b. glass “fibrous or filamentary materials” having a “specific modulus” of $3,18 \times 10^6$ m or greater and a “specific tensile strength” of $76,2 \times 10^3$ m or greater; or
- c. thermoset resin impregnated continuous “yarns”, “rovings”, “tows” or “tapes” with a width no greater than 15 mm (prepregs), made from carbon or glass “fibrous or filamentary materials” specified in 1C210.a or b.

Technical note:

The resin forms the matrix of the composite.

Note: In 1C210, “fibrous or filamentary materials” is restricted to continuous “monofilaments”, “yarns”, “rovings”, “tows” or “tapes”.

3.15. 1C230 For this entry, substitute the following:

‘1C230 Beryllium metal, alloys containing more than 50 % of beryllium by weight, beryllium compounds, or manufactures thereof;

except:

- a. metal windows for X-ray machines, or for bore-hole logging devices;
- b. oxide shapes in fabricated or semi-fabricated forms specially designed for electronic component parts or as substrates for electronic circuits;
- c. beryl (silicate of beryllium and aluminium) in the form of emeralds or aquamarines.

Note: 1C230 includes waste and scrap containing beryllium as defined above.’

3.16. 1C232 For this entry, substitute the following:

‘1C232 Helium-3 or helium isotopically enriched in the helium-3 isotope, mixtures containing helium-3, or products or devices containing any of the foregoing;

except:

a product or device containing less than 1 g of helium-3.’

3.17. 1C233 For this entry, substitute the following:

‘1C233 Lithium enriched in the 6 isotope (^6Li) to greater than 7,5 atom percent, alloys, compounds or mixtures containing lithium enriched in the 6 isotope, or products or devices containing any of the foregoing;

except:

thermoluminescent dosimeters.

Technical note:

The natural occurrence of the 6 isotope in lithium is 7,5 atom percent.’

- 3.18. 1C234 For this entry, substitute the following:
- ‘1C234 Zirconium with a hafnium content of less than 1 part hafnium to 500 parts zirconium by weight, in the form of metal, alloys containing more than 50 % zirconium by weight, or compounds, or manufactures wholly thereof;
- except:
- zirconium in the form of foil having a thickness not exceeding 0,10 mm.
- Note: 1C234 includes waste and scrap containing zirconium as defined here.*
- 3.19. 1C235 For this entry, substitute the following:
- ‘1C235 Tritium, tritium compounds, mixtures containing tritium in which the ratio of tritium to hydrogen by atoms exceeds 1 part in 1 000, or products or devices containing any of the foregoing;
- except:
- a product or device containing not more than $1,48 \times 10^3$ GBq (40 Ci) of tritium in any form.’
- 3.20. 1C236 For this entry, substitute the following:
- ‘1C236 Alpha-emitting radionuclides having an alpha half-life of 10 days or greater but less than 200 years, compounds or mixtures containing any of these radionuclides with a total alpha activity of 37 GBq/kg (1 Ci/kg) or greater, or products or devices containing any of the foregoing;
- except:
- a product or device containing less than 3,7 GBq (100 millicuries) of alpha activity.’
- 3.21. 1C237 For this entry, substitute the following:
- ‘1C237 Radium-226, radium-226 compounds, mixtures containing radium-226, or products or devices containing any of the foregoing;
- except:
- a. medical applicators;
- b. a product or device containing not more than 0,37 GBq (10 millicuries) of radium-226 in any form.’
- 3.22. 1C240 After entry 1C239, insert the following new entry:
- ‘1C240 Nickel powder or porous nickel metal, other than those specified in 0C006, as follows:
- a. powder with a nickel purity content of 99,0 % by weight or greater and a mean particle size of less than 10 micrometres measured by American Society for Testing and Materials (ASTM) B330 standard;
- except:
- filamentary nickel powders;
- b. porous nickel metal produced from materials specified in 1C240.a;
- except:
- single porous nickel sheets not exceeding 1 000 cm² per sheet.
- Note: 1C240.b refers to porous metal formed by compacting and sintering the materials in 1C240.a to form a metal material with fine pores interconnected throughout the structure.*
- 3.23. 1C350 For this entry, substitute the following:
- ‘1C350 Chemicals, which may be used as precursors for toxic chemical agents, as follows:
- NB: *See also Military Goods Controls.*
1. thioglycol (111-48-8);
 2. phosphorus oxychloride (10025-87-3);
 3. dimethyl methylphosphonate (756-79-6);
 4. *See Military Goods Controls for methyl phosphonyldifluoride (676-99-3);*
 5. methyl phosphonyl dichloride (676-97-1);
 6. dimethylphosphite (868-85-9);
 7. phosphorus trichloride (7719-12-2);

8. trimethyl phosphite (121-45-9);
9. thionyl chloride (7719-09-7);
10. 3-hydroxy-1-methylpiperidine (3554-74-3);
11. N,N-diisopropyl-(beta)-aminoethyl chloride (96-79-7);
12. N,N-diisopropyl-(beta)-aminoethane thiol (5842-07-9);
13. 3-quinuclidinol (1619-34-7);
14. potassium fluoride (7789-23-3);
15. 2-chloroethanol (107-07-3);
16. dimethylamine (124-40-3);
17. diethyl ethylphosphonate (78-38-6);
18. diethyl-N,N-dimethylphosphoramidate (2404-03-7);
19. diethyl phosphite (762-04-9);
20. dimethylamine hydrochloride (506-59-2);
21. ethyl phosphinyl dichloride (1498-40-4);
22. ethyl phosphonyl dichloride (1066-50-8);
23. ethyl phosphonyl difluoride (753-98-0);
24. hydrogen fluoride (7664-39-3);
25. methyl benzilate (76-89-1);
26. methyl phosphinyl dichloride (676-83-5);
27. N,N-diisopropyl-(beta)-amino ethanol (96-80-0);
28. pinacolyl alcohol (464-07-3);
29. *See Military Goods Controls for*
o-ethyl-2-diisopropylaminoethyl methylphosphonite (57856-11-8);
30. triethyl phosphite (122-52-1);
31. arsenic trichloride (7784-34-1);
32. benzilic acid (76-93-7);
33. diethyl methylphosphonite (15715-41-0);
34. dimethyl ethylphosphonate (6163-75-3);
35. ethyl phosphinyl difluoride (430-78-4);
36. methyl phosphinyl difluoride (753-59-3);
37. 3-quinuclidone (3731-38-2);
38. phosphorus pentachloride (10026-13-8);
39. pinacolone (75-97-8);
40. potassium cyanide (151-50-8);
41. potassium bifluoride (7789-29-9);
42. ammonium hydrogen fluoride (1341-49-7);
43. sodium fluoride (7681-49-4);
44. sodium bifluoride (1333-83-1);
45. sodium cyanide (143-33-9);
46. triethanolamine (102-71-6);
47. phosphorus pentasulphide (1314-80-3);
48. di-isopropylamine (108-18-9);
49. diethylaminoethanol (100-37-8);
50. sodium sulphide (1313-82-2);
51. sulphur monochloride (10025-67-9);
52. sulphur dichloride (10545-99-0);
53. triethanolamine hydrochloride (637-39-8);
54. N,N-diisopropyl-(beta)-aminoethyl chloride hydrochloride (4261-68-1).'

3.24. 1C351 For this entry, substitute the following:

'1C351 Human pathogens, zoonoses and "toxins", as follows:

- a. viruses, whether natural, enhanced or modified, either in the form of "isolated live cultures" or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:
 1. Chikungunya virus;
 2. Congo-Crimean haemorrhagic fever virus;
 3. dengue fever virus;
 4. eastern equine encephalitis virus;
 5. ebola virus;
 6. hantaan virus;
 7. junin virus;
 8. lassa fever virus;
 9. lymphocytic choriomeningitis virus;
 10. Machupo virus;
 11. Marburg virus;
 12. monkey pox virus;
 13. Rift Valley fever virus;
 14. tick-borne encephalitis virus (Russian spring-summer encephalitis virus);
 15. Variola virus;
 16. Venezuelan equine encephalitis virus;
 17. western equine encephalitis virus;
 18. white pox;
 19. yellow fever virus;
 20. Japanese encephalitis virus;
- b. rickettsiae, whether natural, enhanced or modified, either in the form of "isolated live cultures" or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:
 1. *coxiella burnetii*;
 2. *rickettsia quintana*;
 3. *rickettsia prowasecki*;
 4. *rickettsia rickettsii*;
- c. bacteria, whether natural, enhanced or modified, either in the form of "isolated live cultures" or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:
 1. *bacillus anthracis*;
 2. *brucella abortus*;
 3. *brucella melitensis*;
 4. *brucella suis*;
 5. *chlamydia psittaci*;
 6. *clostridium botulinum*;
 7. *francisella tularensis*;
 8. *pseudomonas mallei*;
 9. *pseudomonas pseudomallei*;
 10. *salmonella typhi*;
 11. *shigella dysenteriae*;
 12. *vibrio cholerae*;
 13. *yersinia pestis*;

d. "toxins", as follows:

1. botulinum toxins;
2. *clostridium perfringens* toxins;
3. conotoxin;
4. ricin;
5. saxitoxin;
6. shiga toxin;
7. *staphylococcus aureus* toxins;
8. tetrodotoxin;
9. verotoxin;
10. microcystin (cyanginosin);

except:

any goods specified in 1C351 in the form of a vaccine.'

3.25. 1C352 For this entry, substitute the following:

'1C352 Animal pathogens, as follows:

a. viruses, whether natural, enhanced or modified, either in the form of "isolated live cultures" or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:

1. African swine fever virus;
2. avian influenza virus, which are:
 - a. uncharacterized; or
 - b. defined in Community Directive 92/40/EEC (OJ No L 16, 23. 1. 1992, p. 19) as having high pathogenicity, as follows:
 1. type A viruses with an IVPI (intravenous pathogenicity index) in six-week old chickens of greater than 1,2;
or
 2. type A viruses H5 or H7 subtype for which nucleotide sequencing has demonstrated multiple basic amino acids at the cleavage site of haemagglutinin;
3. bluetongue virus;
4. foot-and-mouth disease virus;
5. goat pox virus;
6. porcine herpes virus (Aujeszky's disease);
7. swine fever virus (hog cholera virus);
8. lyssa virus;
9. Newcastle disease virus;
10. peste des petits ruminants virus;
11. porcine enterovirus type 9;
12. rinderpest virus;
13. sheep pox virus;
14. teschen disease virus;
15. vesicular stomatitis virus;

b. mycoplasma mycoides, whether natural, enhanced or modified, either in the form of "isolated live cultures" or as material including living material which has been deliberately inoculated or contaminated with such mycoplasma mycoides;

except:

any goods specified in 1C352 in the form of a vaccine.'

3.26. 1E103 '... the production of composites or partially processed composites.' should be '... the "production" of "composites" or partially processed "composites".'

3.27. 1E104 '... the production of ...' should read '... the "production" of ...'.

3.28. 1E104 NOTE 'This item ...' should be '1E104 ...'.

- 3.29. 1E201 For this entry, substitute the following:

'1E201 "Technology" according to the General Technology Note for the "use" of goods specified in 1A002, 1A202, 1A225 to 1A227, 1B201, 1B225 to 1B233, 1C002a.2.c or d, 1C010.b, 1C202, 1C210, 1C216, 1C225 to 1C240 or 1D201.'

4. CATEGORY 2

- 4.1. 2A226 For this entry, substitute the following:

'2A226 Valves 5 mm or greater in "nominal size", with a bellows seal, wholly made of or lined with aluminium, aluminium alloy, nickel, or alloy containing 60 % or more nickel, either manually or automatically operated.

Note: For valves with different inlet and outlet diameters, the "nominal size" above refers to the smallest diameter.'

- 4.2. 2B001.a. Note a. '...this item; ...' should be '...2B001; ...'.

- 4.3. 2B001.a. Note b. '...this item; ...' should be '...2B001; ...'.

- 4.4. 2B001.c.4. Technical note '...this item; ...' should be '...2B001; ...'.

- 4.5. 2B115 Technical Note 1 '...this item; ...' should be '...2B115 ...'.

- 4.6. 2B116 For this entry, substitute the following:

'2B116 Vibration test systems, equipment and components therefor, as follows:

- a. vibration test systems employing feedback or closed loop techniques and incorporating a digital controller, capable of vibrating a system at 10 g rms or more over the entire range 20 to 2 000 Hz and imparting forces of 50 kN, measures "bare table", or greater;
- b. digital controllers, combined with specially designed vibration test software, with a "real-time bandwidth" greater than 5 kHz designed for use with vibration test systems specified in 2B116.a;
- c. vibration thrusters (shaker units), with or without associated amplifiers, capable of imparting a force of 50 kN, measures "bare table", or greater and usable in vibration test systems specified in 2B116.a;
- d. test piece support structures and electronic units designed to combine multiple shaker units in a system capable of providing an effective combined force of 50 kN, measured "bare table", or greater, and usable in vibration systems specified in 2B116.a.

Note: In 2B116 'bare table' means a flat table, or surface, with no fixture or fittings.'

- 4.7. 2B204 For this entry, substitute the following:

'2B204 "Isostatic presses", other than those specified in 2B004 or 2B104, capable of achieving a maximum working pressure of 69 MPa or greater and having a chamber cavity with an inside diameter in excess of 152 mm, and specially designed dies, moulds or controls therefor.

Technical note:

The inside chamber dimension is that of the chamber in which both the working temperature and the working pressure are achieved and does not include fixtures. That dimension will be the smaller of either the inside diameter of the pressure chamber or the inside diameter of the insulated furnace chamber, depending on which of the two chambers is located inside the other.'

- 4.8. 2B207 For this entry, substitute the following:
- ‘2B207 “Robots” or “end-effectors”, other than those specified in 2B007, specially designed to comply with national safety standards applicable to handling high explosives (for example, meeting electrical code ratings for high explosives) and specially designed controllers therefor.’
- 4.9. 2B215 For this entry, substitute the following:
- ‘2B215 Flow-forming machines, or spin-forming machines capable of flow-forming functions, other than those specified in 2B115, or mandrels as follows:
1. having three or more rollers (active or guiding); and
 2. according to the manufacturer’s technical specification can be equipped with “numerical control” units or a computer control;
 - b. rotor-forming mandrels designed to form cylindrical rotors of inside diameter between 75 mm and 400 mm.
- Note: 2B215 includes machines which have only a single roller designed to deform metal plus two auxiliary rollers which support the mandrel, but do not participate directly in the deformation process.’*
- 4.10. 2B225 For this entry, substitute the following:
- ‘2B225 Remote manipulators that can be used to provide remote actions in radiochemical separation operations and hot cells, as follows:
- a. having a capability of penetrating 0,6 m or more of hot cell wall (through-the-wall operation); or
 - b. having a capability of bridging over the top of a hot cell wall with a thickness of 0,6 m or more (over-the-wall operation).
- Note: Remote manipulators provide translation of human operator actions to a remote operating arm and terminal fixture. They may be of “master/slave” type or operated by joystick or keypad.’*
- 4.11. 2B226 For this entry, substitute the following:
- ‘2B226 Vacuum or controlled environment (inert gas) induction furnaces capable of operation above 1 123 K (850 °C) and having induction coils 600 mm or less in diameter, and designed for power inputs of 5 kW or more, and power supplies specially designed therefor with a specified power output of 5 kW or more.
- NB: See also 3B.*
- Note: 2B226 does not control furnaces designed for the processing of semiconductor wafers.’*
- 4.12. 2B230 For this entry, substitute the following:
- ‘2B230 “Pressure transducers” which are capable of measuring absolute pressure at any point in the range 0 to 13 kPa, with pressure sensing elements made of or protected by nickel, nickel alloys with more than 60 % nickel by weight, aluminium or aluminium alloys, having any of the following:
- a. a full scale of less than 13 kPa and an accuracy of better than $\pm 1\%$ (full-scale); or
 - b. a full scale of 13 kPa or greater and an accuracy of better than ± 130 Pa.
- Technical note:*
- For the purposes of 2B230, “accuracy” includes non-linearity, hysteresis and repeatability at ambient temperature.’*

- 4.13. 2B231 For this entry, substitute the following:

'2B231 Vacuum pumps with an input throat size of 380 mm or greater with a pumping speed of 15 000 litres/s or greater and capable of producing an ultimate vacuum better than 13 mPa.

Technical notes:

1. *The ultimate vacuum is determined at the input of the pump with the input of the pump blocked off.*
2. *The pumping speed is determined at the measurement point with nitrogen gas or air.*

- 4.14. 2B352.f.2. Note 'In this entry, ...' should be 'In 2B352.f.2, ...'.

5. CATEGORY 3

- 5.1. 3A001.a.2. For this sub-entry, substitute the following:

2. "microprocessor microcircuits", "microcomputer microcircuits", microcontroller microcircuits, electrical erasable programmable read-only memories (Eeproms), static random-access memories (SRAMs), storage integrated circuits manufactured from a compound semiconductor, analogue-to-digital converters, digital-to-analogue converters, electro-optical or "optical integrated circuits" for "signal processing", field programmable gate arrays, field programmable logic arrays, neural network integrated circuits, custom integrated circuits for which either the function is unknown or the control status of the equipment in which the integrated circuit will be used is unknown, or fast Fourier transform (FFT) processors, as follows:

- a. rated for operation at an ambient temperature above 398 K (125°C); or
- b. rated for operation at an ambient temperature below 218 K (-55°C);
- c. rated for operation over the entire ambient temperature range from 218 K (-55°C) to 398 K (125°C);

Note: 3A001.a.2 does not apply to integrated circuits for civil automobiles or railway train applications.'

- 5.2. 3A001.e.5. 'NB: See also 3A201.c.' should be 'NB: See also 3A101.b and 3A201.c.'

- 5.3. 3A201.b.4. '... volume.' should read '... volume; '.

- 5.4. 3A226 For this entry, substitute the following:

'3A226 Direct current high-power supplies, other than those specified in 0B001.j.6, capable of continuously producing, over a time period of eight hours, 100 V or greater with current output of 500 A or greater and with current or voltage regulation better than 0,1 %.'

- 5.5. 3A227 For this entry, substitute the following:

'3A227 High-voltage direct current power supplies, other than those specified in 0B001.j.5, capable of continuously producing, over a time period of eight hours, 20 000 V or greater with current output of 1 A or greater and with current or voltage regulation better than 0,1 %.'

- 5.6. 3A230 Technical note 'In this item, ...' should be 'In 3A230, ...'.

- 5.7. 3E001 NOTE b.1 '... more, and' should be '... more; and'.

- 5.8. 3E102 '... of software specified ...' should be '... of "software" specified ...'.

6. CATEGORY 4

- 6.1. 4A002.b. '... having any of ...' should be '... having both of ...'.
- 6.2. 4E001 '... 4A or 4D;' should be '... 4A or 4D.'
- 6.3. Technical note on CTP At the end of the last note, '... 0,75;' should read '... 0,75.'

7. CATEGORY 5

- 7.1. 5A001.c.5. Insert on a new line at the end of the sub-entry, the following note:
'Note: 5A001.c.5 does not apply to networks using only "network access controllers" or to "network access controllers" themselves.'
- 7.2. 5A001.c.6. The note should be as follows:
'Note: 5A001.c.6 does not apply to networks using only "network access controllers" or to "network access controllers" themselves.'

8. CATEGORY 6

- 8.1. 6A002.c.1. '... 6A002.a.2.' should be '... 6A002.a.2.a.'
- 8.2. 6A005 In the heading, "Lasers", components ...' should be "Lasers", other than those specified in 0B001.g.5. or 0B001.h.6., components ...'.
- 8.3. 6A005.f.2. '... specified "lasers"; ...' should be '... "lasers" specified in 6A005;'.
'
- 8.4. 6A203.a. For this sub-entry, substitute the following:
'a. mechanical rotating mirror cameras, as follows, and specially designed components therefor:
1. framing cameras with recording rates greater than 225 000 frames per second;
or
2. streak cameras with writing speeds greater than 0,5 mm per microsecond;
Note: Components of such cameras include their synchronizing electronic units and rotor assemblies consisting of turbines, mirrors and bearings.'
- 8.5. 6A203.c. For this sub-entry, substitute the following:
'c. radiation-hardened TV cameras, or lenses therefor, specially designed or rated as radiation hardened to withstand greater than 50×10^3 grays (Silicon) (5×10^6 rad (Silicon)) without operational degradation.'
- 8.6. 6A205 In the heading, '... specified in 6A005, ...' should be '... specified in 0B001.g.5, 0B001.h.6 or 6A005, ...'.

9. CATEGORY 7

- 9.1. 7A115 Note 'This item includes ...' should be '7A115 includes ...'.
- 9.2. 7D003.c. '... expert systems;' should be '... "expert systems";'.
- 9.3. 7E004.b.6. '... expert systems;' should be '... "expert systems";'.

10. CATEGORY 8

- 10.1. 8A001.i.2. Technical note '... draft ...' should be '... draught ...'.

11. CATEGORY 9

11.1. 9A007.d. For this sub-entry, substitute the following:

- 'd. insulation and propellant bonding systems using direct-bonded motor designs to provide a "strong mechanical bond" or a barrier to chemical migration between the solid propellant and case insulation material.

Technical note:

In 9A007.d, a "strong mechanical bond" means bond strength equal to or more than propellant strength.'

11.2. 9A008.a. For this sub-entry, substitute the following:

- 'a. insulation and propellant bonding systems using liners to provide a "strong mechanical bond" or a barrier to chemical migration between the solid propellant and case insulation material;

Technical note:

In 9A008.a, a "strong mechanical bond" means bond strength equal to or more than propellant strength.'

11.3. 9A106.d. Note '... in this item' should be '... in 9A106.d ...'.

11.4. 9B106.a.1. '... 10 g RMS ...' should be '... 10 g rms ...'.

11.5. 9E003.a.1. For this sub-entry, substitute the following:

- '1. gas turbine blades, vanes or tip shrouds made from directionally solidified or single crystal alloys having (in the 001 Miller index direction) a stress-rupture life exceeding 400 hours at 1 273 K (1 000°C) at a stress of 200 MPa, based on the average property values;'

11.6. 9E003.a.2. Delete this sub-entry.

11.7. 9E003.a.3. Re-designate this sub-entry 9E003.a.2.

11.8. 9E003.a.4. Re-designate this sub-entry 9E003.a.3.

11.9. 9E003.a.5. Re-designate this sub-entry 9E003.a.4.

11.10. 9E003.a.6. Re-designate this sub-entry 9E003.a.5.

11.11. 9E003.a.7. Re-designate this sub-entry 9E003.a.6.

11.12. 9E003.a.8. Re-designate this sub-entry 9E003.a.7.

11.13. 9E003.a.9. Re-designate this sub-entry 9E003.a.8.

11.14. 9E003.a.10. Re-designate this sub-entry 9E003.a.9.

11.15. 9E003.a.11. Re-designate this sub-entry 9E003.a.10.

11.16. 9E003.a.12. Re-designate this sub-entry 9E003.a.11.

11.17. 9E003.a.13. Re-designate this sub-entry 9E003.a.12.

11.18. 9E003.a.14. Re-designate this sub-entry 9E003.a.13.

ANNEX II

The list contained in Annex IV to Decision 94/942/CFSP shall be amended as follows:

- in the category 'Community Strategic Control', item 4A003.b should read:

'4A003.b. Only computers with "supercomputer" performance, i.e. computers that have a "composite theoretical performance" (CTP) of 10 000 million theoretical operations per second (MTOPS) or greater;'
 - in the category 'MTCR Technology':
 - item 9E001 should read:

"Technology" for the "development" of equipment specified in 9A005, 9A007.a.1, 9A008.d, 9B115 and 9B116;'
 - item 9E002 should read:

"Technology" for the "production" of equipment specified in 9A005, 9A007.a.1, 9A008.d, 9B115 and 9B116;'
 - after entry 9E002, the following new entry should be inserted:

'9E101 "Technology" for the "development" or "production" of equipment specified in 9A108.c or 9A119.'
-

CORRIGENDA

Corrigendum to Council Regulation (EC) No 3381/94 of 19 December 1994 setting up a Community regime for the control of exports of dual-use goods*(Official Journal of the European Communities No L 367 of 31 December 1994)*

On page 1, first recital, fourth line from the end:

for: '... regime of exports controls ...',

read: '... regime of export controls ...'.

On page 2, fourth recital, penultimate line:

for: 'controls om dual-use ...',

read: 'controls on dual-use ...'.

On page 3 in Article 4 (3), fourth line:

for: '... are intended. wholly or in part, ...',

read: '... are intended, wholly or in part, ...'.

On page 4 in Article 7 (3), sixth line:

for: '... immediately engange',

read: '... immediately engage';

in Article 8, third line:

for: 'consideration in in the common ...',

read: 'consideration in the common ...';

in Article 9 (2), ninth line:

for: '... the relevante indormation',

read: '... the relevant information'.

On page 5 in Article 13 (1), first line:

for: '1. Acting in liason with ...',

read: '1. Acting in liaison with ...';

in Article 13 (2), seventh line:

for: 'confidentiality of information ...',

read: 'confidentiality of information ...';

in Article 14 (1), second indent:

for: '— the quantitiy of ...',

read: '— the quantity of ...';

in Article 15 (b), second line:

for: '... include in paritcular the',

read: '... include in particular the'.

On page 6 in Article 18, first subparagraph, last line; Article 19 (1) or (a) second line and (b) second line:

for: '94/942/PESC',

read: '94/942/CFSP';

in Article 19 (1) (a) second line:

for: '... relevant commerical documents',

read: '... relevant commercial documents'.

Corrigendum to Council Decision 94/942/CFSP of 19 December 1994 on the joint action adopted by the Council on the basis of Article J.3 of the Treaty on European Union concerning the control of exports of dual-use goods

(Official Journal of the European Communities No L 367 of 31 December 1994)

On page 8, Article 1, first subparagraph, first line:

for: '... Member State's',

read: '... Member States'.

On page 10, Nuclear Technology Note, last paragraph, and General Technology Note, last paragraph:

for: '... or the basic scientific ...',

read: '... or to basic scientific ...'.

On page 11, definition 9, last line:

for: '... bit rate (CCITT) recommendation L.113).',

read: '... bit rate (CCITT recommendation L.113).'.

On page 12, definition 17, first line:

for: '... (circle of equal probability (7) ...',

read: '... (circle of equal probability) (7) ...'.

On page 14, definition 36, second line:

for: '... design analyses design concepts ...',

read: '... design analyses, desgin concepts ...'.

On page 15, definition 41, last line:

for: '... internal space.',

read: '... inertial space.'.

On page 23, definition 133, first line:

for: '... means bars ingots, or rods ...',

read: '... means bars, ingots or rods ...'.

On page 27, definitions 152 and 153:

for: '... (296+2) K ((23+2)°C) and a relative humidity of (50+5) %.',

read: '... (296±2) K ((23±2)°C) and a relative humidity of (50±5) %.'.

On page 28, definition 155, first line:

for: '... to "sofidify rapidly" a molten ...',

read: '... to "solidify rapidly" a molten ...'.

On page 30, definition 181, third line:

for: '... more than the ration of the isotope ...',

read: '... more than the ratio of the isotope ...'.

On page 32, 0B001.c.3.c, first and second lines:

for: '... 3,18 × 10⁶ m and ...',

read: '... 3,18 × 10⁶ m and ...';

0B001.c.8, first line:

for: '... and 400 m diameter ...',

read: '... and 400 mm diameter ...'.

On page 33, 0B001.d.1, second and third lines:

for: '... with separates ...',

read: '... which separates ...';

0B001.d.5, last line:

for: '... at pressures kPa or less;',

read: '... at pressures of 600 kPa or less;';

0B001.e.1, first line:

for: '... centrifugal contractors with ...',

read: '... centrifugal contactors with ...'.

On page 35, 0B001.h.5.b:

for: '... of --120°C or less;',

read: '... of -120°C or less;';

0B002, second line:

for: '... plant specific in 0B001 ...',

read: '... plant specified in 0B001 ...'.

On page 37, 0B006.b, third line:

for: '... high corrosive liquids ...',

read: '... highly corrosive liquids ...';

0B006.e, note, point 2:

for: '... diameter or 175 mm ...',

read: '... diameter of 175 mm ...'.

On page 38, 0C003.a, first line:

for: 'a. pllotonium in any form ...',

read: 'a. plutonium in any form ...';

0C003.b, first line:

for: 'b. "Previously seperated" ...',

read: 'b. "previously separated" ...'.

On page 41, 1B001.c, last line:

for: '... modified to the above end-uses;',

read: '... modified for the above end-uses;'.

On page 43, 1B230.c:

for: '... than 8;5 m³/hr.',

read: '... than 8,5 m³/hr.'.

On page 44, 0C001.c, second line:

for: '... /Siemens per metre) ...',

read: '... (Siemens per metre) ...'.

On page 46, 0C005.a.2, first line:

for: '... less than 0,28 × 1⁻⁴ mm² ...',

read: '... less than 0,28 × 10⁻⁴ mm² ...';

1C006.c, second line:

for: '... of 20 micrometre or larger in size per 200 ml and ...',

read: '... of 200 micrometre or larger in size per 100 ml and ...'.

On page 47, 1C006.c, technical note, point d, fifth line:

for: '... 644 6K (371 6°C) ...',

read: '... 644±6K (371±6°C) ...';

1C007.e, second line:

for: '... specified in 1C002.c., as follows:',

read: '... specified in 1C007.c, as follows:'.

On page 49, 1C010.e.2.d, first line:

for: '... specified in 1C008 or 1C009,b, or ...',

read: '... specified in 1C008 or 1C009.b., or ...'.

On pages 52 and 53, 1C350:

— point 4

for: '... 676-99-)',

read: '... (676-99-3)';

— point 24

for: '... (7664-93-3)',

read: '... (7664-39-3)';

— point 34

for: '... ethylphosphonte',

read: '... ethylphosphonate';

— point 50

for: 'sodium sulphie ...',

read: 'sodium sulphide ...'.

On page 54, 1C351.d.10:

for: '10. microcrystin cyanginosin)',

read: '10. microcystin (cyanginosin)';

1C352.a2.b, second line:

for: 'pathogenicity, as follows:',

read: 'pathogenicity, as follows:';

1C353.a, last line:

for: '... or 1C3354;',

read: '... or 1C354;'.

On page 56, 1E002.c:

The text of this subentry should be replaced by the following:

'c. "Technology", for the design or "production" of the following base materials or non-"composite" ceramic materials:

1. Base materials having all of the following characteristics:

a. Any of the following compositions:

1. Single or complex oxides of zirconium and complex oxides of silicon or aluminium;
2. Single nitrides of boron (cubic crystalline forms);
3. Single or complex carbides of silicon or boron; or
4. Single or complex nitrides of silicon;

- b. Total metallic impurities, excluding intentional additions, of less than:
 - 1. 1 000 ppm for single oxides or carbides; or
 - 2. 5 000 ppm for complex compounds or single nitrides; and
- c. 1. Average particle size equal to or less than 5 micrometre and no more than 10 % of the particles larger than 10 micrometre; or
Note: For zirconia, these limits are 1 micrometre and 5 micrometres respectively.
 - 2. a. Platelets with a length to thickness ratio exceeding 5;
 - b. Whiskers with a length to diameter ratio exceeding 10 for diameters less than 2 micrometres; and
 - c. Continuous or chopped fibres less than 10 micrometres in diameter;
- 2. Non-“composite” ceramic materials (except abrasives) composed of the materials described in 1E002.c.1.;

1E101, second line:

for: ‘... 1C117, 1D101 or’,

read: ‘... 1C117, 1D101 or’.

On page 60, 2B001.b.3:

for: ‘... described in 2B001.a.2.B;’,

read: ‘... described in 2B001.a.2.b;’.

On page 62, 2B002.b.1:

for: ‘... than 0,0003 mm TIR; and’,

read: ‘... than 0,0004 mm TIR; and’.

On page 64, 2B006.a.2, second line:

for: ‘(1,25 + L/1,000) micrometre ...’,

read: ‘... (1,25 + (L/1 000)) micrometre ...’.

On page 65, 2B008.d.1, first and second line:

for: ‘... (reference: ISO/DIS 230/t) over full travel;’,

read: ‘... (reference: ISO/DIS 230/1) over full travel;’.

On page 70, 2B352.a, technical note, first line:

for: ‘P3 or P4 (BL4, L3, L4) containment ...’,

read: ‘P3 or P4 (BL3, BL4, L3, L4) containment ...’.

On page 82, 3A001.a.4, first line, and 3A001.a.4.a, first line:

for: ‘... Eeproms ...’,

read: ‘... EEPROMs ...’;

3A001.a.5.b, first and second line:

for: ‘... and a “setting time” of less ...’,

read: ‘... and a “settling time” of less ...’;

3A001.a.12.b, second line:

for: ‘less than $N \log_2 N/10$ 240 ms, where ...’,

read: ‘less than $N \log_2 (N/10240)$ ms, where ...’.

On page 84, 3A001.d.2, last line:

for: ‘ 10^{14} J, or’,

read: ‘ 10^{-14} J, or’.

On page 85, 3A001.e.3.c, second line:

for: '... more than 300 A/mm₂;',

read: '... more than 300 A/mm²;'.

3A001.e.4.b:

for: '... density of 1MJ/m³ or more ...',

read: '... density of 1MJ/m³ or more ...'.

On page 86, 3A101, first line:

for: 'Electronic equipment devices ...',

read: 'Electronic equipment, devices ...'.

On page 88, 3A202.b.1:

for: '... of 1GHz; or',

read: '... of 1GHz or greater; or'.

On page 93, 3E101, second line:

for: '... 3A202 or 3D101.',

read: '... 3A101 or 3D101.'

On page 96, 4A003.f, note, first line:

for: '... the purpose of 4A003.,',

read: '... the purpose of 4A003.f,'.

On page 104, 5A001.a.3, first line:

for: '... 218 K (- 55 °) to 397',

read: '... 218 K (- 55 °C) to 397';

5A001.b, note, point a.9:

for: '... (see CCITT Reg. G. 701);',

read: '... (see CCITT Rec. G. 701);'.

On page 105, 5A001.b.3.a, first line:

for: '... "bandwidth on one voice channel" ...',

read: '... "bandwidth of one voice channel" ...'.

On page 110, 5A002, note, point d, first line:

for: '... or use with commercial',

read: '... for use with commercial';

5B002.a.1, first line:

for: '... equipment of functions ...',

read: '... equipment or functions ...'.

On page 111, 5D002.b:

for: '... specified in 6E002.',

read: '... specified in 5E002.';

5D002.c.1, second line:

for: '... in 5D002 or 5B002;',

read: '... in 5A002 or 5B002;'.

On page 112, fourth line:

for: '6001 Acoustics',

read: '6A001 Acoustics'.

On page 115, 6A002.a.2.a.1, first line:

for: '... exceeding 30 nm but not ...',

read: '... exceeding 400 nm but not ...'.

On page 116, 6A002.b.1:

for: '... less than 20 microradians; or',

read: '... less than 200 microradians; or'.

On page 121, 6A005.c.1.b, first line:

for: '... of 60 nm or more ...',

read: '... of 600 nm or more ...'.

On page 124, 6A006.h.3.b, first and second line:

for: '... exceeding 1×10 magnetic flux quanta per second;',

read: '... exceeding 1×10^6 magnetic flux quanta per second;';

6A07:

for: '6A07',

read: '6A007'.

On page 125, 6A008.b:

for: '... exceeding 6,25 % of the ...',

read: '... exceeding $\pm 6,25$ % of the ...'.

On page 128, 6A205.d, second line:

for: '... of less than 20 ns operating ...',

read: '... of less than 200 ns operating ...';

6B004.a, first line:

for: '... an accuracy of 0,1 % of the ...',

read: '... an accuracy of $\pm 0,1$ % of the ...';

6B004, note:

for: '... 6B003 does not ...',

read: '... 6B004 does not ...'.

On page 135, 7D103, note, second line:

for: '... specified in 4A202.',

read: '... specified in 4A102.';

7E003, second line:

for: '... specified in 7A002 to 7A004 ...',

read: '... specified in 7A001 to 7A004 ...'.

On page 136, 7E004.a.4, second line:

for: 'specified in 7A002 or 7A002.',

read: 'specified in 7A001 or 7A002.'.

On page 138, 8A001.b:

The text of 8A001.b should be replaced by the following:

'b. Manned, untethered submersible vehicles:

1. Designed to "operate autonomously" and having a lifting capacity of:
 - a. 10 % or more of their weight in air; and
 - b. 15 kN or more;
2. Designed to operate at depths exceeding 1 000 m; or
3.
 - a. Designed to carry a crew of four or more;
 - b. Designed to "operate autonomously" for 10 hours or more;
 - c. Having a "range" of 25 nautical miles or more; and
 - d. Having a length of 21 m or less;'

On page 145, 9A008.d.2:

for: '... of 20o/s or more ...',

read: '... of 20° /s or more ...';

9A008.d.3:

for: '... of 40o/s² or more.',

read: '... of 40° /s² or more.'

On page 147, 9A1110, sixth and seventh lines:

for: '... greater than 3,18×10⁶ m.',

read: '... greater than 3,18×10⁶ m.';

9A1116, first line:

for: '... vehicles, usable in "missiles" and ...',

read: '... vehicles, usable in "missiles", and ...'.

On page 149, 9B009, first line:

for: 'Tooling specially ...',

read: 'Tooling specially ...'.

Corrigendum to Council Decision 95/127/CFSP of 10 April 1995 amending Decision 94/942/CFSP on the joint action adopted by the Council on the basis of Article J.3 of the Treaty on European Union concerning the control of exports of dual-use goods

(Official Journal of the European Communities No L 90 of 21 April 1995)

On page 2 in Article 1, new Article 8, first line:

for: '...enter into fore on the day ...',

read: '...enter into force on the day ...'.
