

Official Journal

of the European Communities

ISSN 0378-6978

L 172

Volume 40

30 June 1997

English edition

Legislation

Contents

I *Acts whose publication is obligatory*

- ★ Council Regulation (EC) No 1186/97 of 27 June 1997 amending the Annex to Regulation (EC) No 1255/96 temporarily suspending the autonomous Common Customs Tariff duties on certain industrial and agricultural products 1

I

(Acts whose publication is obligatory)

COUNCIL REGULATION (EC) No 1186/97

of 27 June 1997

amending the Annex to Regulation (EC) No 1255/96 temporarily suspending the autonomous Common Customs Tariff duties on certain industrial and agricultural products

THE COUNCIL OF THE EUROPEAN UNION,

Whereas, for the sake of clarity, it is therefore advisable to regard the products for which amendments to the description are required as new products,

Having regard to the Treaty establishing the European Community, and in particular Article 28 thereof,

HAS ADOPTED THIS REGULATION:

Having regard to the proposal from the Commission,

Article 1

Having regard to Regulation (EC) No 1255/96 ⁽¹⁾,

The products set out in Annex I to this Regulation shall be added to the Annex to Regulation (EC) No 1255/96. The autonomous Common Customs Tariff duties on these products shall be suspended at the rate indicated for each product.

Whereas it is in the interest of the Community to suspend partially or totally the autonomous Common Customs Tariff duties for a number of new products not listed in the Annex to the said Regulation;

Article 2

The products for which the codes are set out in Annex II to this Regulation shall be removed from the Annex to Regulation (EC) No 1255/96.

Whereas the products referred to in the said Regulation, for which it is no longer in the Community's interest to maintain suspension of autonomous Common Customs Tariff duties or for which it is necessary to amend the description in the light of technical developments, must be withdrawn from the list in the Annex thereto;

Article 3

This Regulation shall enter into force on 1 July 1997.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Luxembourg, 27 June 1997.

For the Council

The President

A. JORRITSMA-LEBBINK

⁽¹⁾ OJ No L 158, 29. 6. 1996, p. 1. Regulation as last amended by Regulation (EC) No 2484/96 (OJ No L 341, 30. 12. 1996, p. 1).

ANNEX I

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 1518 00 91	10	Soya-bean oil, modified with maleic acid, for the manufacture of cosmetic products (a)	0
ex 2820 90 90	10	Manganese (II,III) oxide containing by weight 70 % or more of manganese	0
ex 2821 10 00	10	Diiron trioxide, in the form of powder, of a purity by weight of 99,2 % or more, for the manufacture of goods of heading No 8504 (a)	0
ex 2823 00 00	20	Titanium dioxide, of a purity by weight of 98,5 % or more, with an average grain-size of 0,2 micrometre or more but not exceeding 1,8 micrometres, for use in the manufacture of synthetic fibres (a)	0
ex 2843 90 90	30	Mixture of palladium phthalocyanines	0
ex 2846 10 00 ex 3824 90 95	10 48	Rare-earth concentrate containing by weight 60 % or more but not more than 75 % of rare-earth oxides and not more than 1 % each of zirconium oxide, aluminium oxide or iron oxide, and having a loss on ignition of 5 % or more by weight	0
ex 2902 90 80	40	1,4-Diethylbenzene	0
2914 21 00		Camphor	0
ex 2914 70 90	30	4,4'-Dibromobenzil	0
ex 2915 40 00	10	Vinyl chloroacetate	0
ex 2917 11 00	20	Bis(<i>p</i> -methylbenzyl) oxalate	0
ex 2918 19 10	10	L-Malic acid	0
ex 2921 44 00	10	Methyldiphenylamine	0
ex 2922 29 00	50	6-Methoxy- <i>m</i> -toluidine	0
ex 2923 90 00	10	Tetramethylammonium hydroxide, in the form of an aqueous solution containing: — 25 ($\pm$ 0,5) % by weight of tetramethylammonium hydroxide, — 500 mg/kg or less of carbonate, — 200 mg/kg or less of chloride and — 5 mg/kg or less of potassium	0
ex 2930 90 70 ex 3824 90 95	50 51	2-Chlorophenylsulfonyl isocyanate, in the form of a solution in xylene	0
ex 2930 90 70 ex 3824 90 95	55 52	Methyl 2-(isocyanatosulfonyl)methylbenzoate, in the form of a solution in xylene	0
ex 2931 00 80	55	Tributylphosphine	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 2931 00 80	65	Bis(2,4,4-trimethylpentyl)phosphinic acid	0
ex 2933 21 00	40	1-[1,3-Bis(hydroxymethyl)-2,5-dioxoimidazolidin-4-yl]-1,3-bis(hydroxymethyl)urea	0
ex 2933 90 95	55	5-Nitroindole	0
ex 2934 20 90	10	4-Chloro-1,3-benzothiazol-2(3H)-one	0
ex 2934 90 60	60	Dimethenamide (ISO)	0
ex 3506 91 00	20	Heat-activated adhesive based on phenolic resin and rubber, in the form of a film on a release paper, for use in the manufacture of brake pads for the automotive industry (a)	0
ex 3702 32 90 ex 3703 90 10	10 10	Paper sheet, coated with silver halide emulsion, for the manufacture of goods of subheading 3701 20 00 (a)	0
ex 3812 30 80	40	Dialuminium tetramagnesium monocarbonate dodecahydroxide monohydrate, coated with a surface-active agent	0
ex 3814 00 90	10	Mixture containing by weight 25 % or more but not more than 35 % of dimethyl sulfoxide and 65 % or more but not more than 75 % of monoethanolamine	3
ex 3815 19 90	30	Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polypropylene (a)	0
ex 3815 90 90	85	Catalyst based on aluminosilicate (zeolite), for the transalkylation of alkylaromatic hydrocarbons (a)	0
ex 3818 00 90	20	Wafers of indium phosphide, doped	0
ex 3824 90 95	49	Mixed oxides of metals, in the form of powder, containing by weight: — 70 % or more but not more than 75 % of iron oxide, — 10 % or more but not more than 20 % of zinc oxide, — 10 % or more but not more than 15 % of magnesium oxide, — 1 % or more but not more than 5 % of manganese oxide and — 1 % or more but not more than 3 % of copper oxide	0
ex 3824 90 95	50	Zeolites consisting of oxides of barium, aluminium and silicon, containing by weight 30 % or more but not more than 40 % of barium oxide, in the form of spheres of which 80 % or more by weight have a diameter of 0,3 mm or more but not more than 1,2 mm	0
ex 3903 90 90	60	Copolymer of styrene with butyl acrylate, butyl methacrylate and methyl methacrylate, of an average molecular weight of 180 000 or more but not exceeding 240 000, in one of the forms mentioned in note 6 (b) of Chapter 39	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 3904 40 00	91	Copolymer of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight: — 87 % or more but not more than 92 % of vinyl chloride, — 2 % or more but not more than 9 % of vinyl acetate and — 1 % or more but not more than 8 % of vinyl alcohol, in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of goods of heading No 8523 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (a)	0
ex 3904 61 90	20	Copolymer of tetrafluoroethylene and perfluorinated propyl vinyl ether, containing 3,2 % or more but not more than 4,6 % by weight of perfluorinated propyl vinyl ether and less than 1 mg/kg of extractable fluoride ions	0
ex 3904 69 90	96	Polychlorotrifluoroethylene, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39	0
ex 3905 91 00	93	Copolymer of ethylene and vinyl alcohol (EVOH)	0
ex 3912 90 10	10	Cellulose acetate propionate, non-plasticized, in the form of powder: — containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method) and — of a viscosity not exceeding 120 poise (as determined by the ASTM D 817-72 method), for the manufacture of printing inks, paints, lacquers and other coatings, and reprographic coatings (a)	0
ex 3917 32 19	10	Flexible pipe of silicone foam, with continuous channels, of a Shore A hardness of 7 or more but not exceeding 48 and a density of 0,28 g/cm ³ or more but not exceeding 0,92 g/cm ³	0
ex 3920 20 90	92	Laminated sheet or strip, consisting of a film of a thickness of 181 micrometres or more but not exceeding 223 micrometres composed of a blend of a copolymer of propylene with ethylene and a copolymer of styrene-ethylene-butylene-styrene (SEBS) coated or covered on one side with a layer of a copolymer of styrene-ethylene-butylene-styrene (SEBS) and a layer of polyester	0
ex 3920 62 19	70	Film of polyethylene terephthalate, coated on both sides with a layer of epoxy acrylic resin, of a total thickness of 37 micrometres ($\pm$ 3 micrometres)	0
ex 3920 69 00	20	Film of polyethylene naphthalene-2,6-dicarboxylate, of a thickness of 82 micrometres or more but not exceeding 88 micrometres	0
ex 3921 19 90	91	Microporous polypropylene film of a thickness not exceeding 100 micrometres	0
ex 4823 90 50	10	Paper coated with dye retention and dye releasing agents used to produce a positive image, for the manufacture of goods of subheading 3701 20 00 (a)	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 7006 00 90	30	Glass plate, uncoated, of dimensions of 320 × 352 mm or more but not exceeding 320 × 400 mm, of a thickness of 0,6 mm or more but not exceeding 1,2 mm, with a flatness deviation not exceeding 25 micrometres, for the manufacture of liquid crystal displays with active matrix (a)	0
ex 7011 20 00	40	Glass face-plate: — with a diagonal measurement of 366,4 mm (± 1,5 mm) and of dimensions of 246,4 × 315,4 mm (± 1,5 mm), — with a diagonal measurement of 391 mm (± 1,5 mm) and of dimensions of 261,4 × 326,8 mm (± 1,5 mm), — with a diagonal measurement of 442 mm (± 1,5 mm) and of dimensions of 293,4 × 369,2 mm (± 1,5 mm), — with a diagonal measurement of 544,5 mm (± 1,6 mm) and of dimensions of 358 × 454 mm (± 1,6 mm), having a cylindrical curvature, or — with a diagonal measurement of 629,8 mm (± 3 mm) and of dimensions of 406,5 × 519 mm (± 2 mm), having a cylindrical curvature, and with a raised edge, for the manufacture of colour cathode-ray tubes (a)	0
ex 7014 00 00	10	Optical elements of glass (other than those of heading No 7015), not optically worked, other than signalling glassware	0
ex 7409 19 00	10	Sheet or plate of polytetrafluoroethylene, with aluminium oxide or titanium dioxide as a filler or reinforced with glass-fibre fabric, laminated on both sides with copper foil	0
ex 8101 99 00	10	Disc (target) with deposition material, of tungsten or an alloy containing by weight 90 % of tungsten and 10 % of titanium, — containing 100 micrograms/kg or less of sodium and — mounted on a copper or aluminium support, for use in the manufacture of goods of heading No 8542 by sputtering (a)	0
ex 8108 90 90	92	Disc (target) with deposition material, of titanium, — containing 50 micrograms/kg or less of sodium and — mounted on a copper or aluminium support, for use in the manufacture of goods of heading No 8542 by sputtering (a)	0
ex 8471 70 51	30	Drive-unit, comprising a printed circuit on which are mounted integrated circuits providing drive-and-signal-processing functions for reading optical CD-ROM discs, not capable of recording	0
ex 8473 30 10	25	Processor, only consisting of: — a central processing unit (CPU), — one or more cache memories (including so-called 'TAG-RAMs'), — resistors and capacitors, the whole mounted on a printed circuit and contained in a housing whether or not with cooling elements	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8473 30 10	80	Microprocessor, microcontroller or microcomputer, only consisting of two monolithic integrated circuits contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): 80521EX COP 87L2 COP 87L4 COP 87L8 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8473 40 10	10	Thermal printer head	0
ex 8473 40 90	85		0
ex 8481 80 59	10	Air control valve, consisting of a stepping motor and a valve pintle, for the regulation of idle air flow in fuel injection engines	0
ex 8504 40 30	10	Direct current to direct current converter	0
ex 8504 40 99	20		0
ex 8542 50 00	08		0
ex 8507 30 91	20	Rectangular accumulator, with a length not exceeding 69 mm, a width not exceeding 36 mm and a thickness not exceeding 12 mm, for use in the manufacture of rechargeable batteries (a)	0
ex 8507 80 91	10		0
ex 8507 80 99	10		0
ex 8507 80 91	40	Cylindrical nickel-hydrid accumulator, with a length of 49,5 mm ($\pm 0,5$ mm) and a diameter of 10 mm ($\pm 0,5$ mm), having a nominal capacity of 540 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
ex 8517 50 90	50	Receive and transmit unit, only for cables with an optical fibre core diameter of 50 or 62,5 μ m, capable of converting light pulses into electrical signals and converting electrical signals into light pulses, capable of operating with a data transfer rate not exceeding 125 Mbits/s, operating at a nominal wavelength of 1 300 nm, comprising a photodiode, a light-emitting diode, an amplifier and a drive circuit, contained in a housing with 13 connections	0
ex 8517 80 90	50		0
ex 8517 90 88	20	Parts, for use in the manufacture or the repair of products falling within subheading 8517 21 00 (a)	0
ex 8548 90 00	40		0
ex 8522 90 98	40	Compact disc changing and selection mechanism, comprising electronic components, not comprising circuits with amplification functions or power supply drive functions, for use in the manufacture of products falling within heading 8527 (a)	0
ex 8529 90 70	94	Receiver providing conversion of radio frequencies (RF) into intermediate frequencies (IF) and analogue-to-digital conversion of satellite positioning signals of 1 575,42 MHz, only consisting of two monolithic integrated circuits mounted on a support and contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): Gemini/Pisces GP00-D227 R6732-12 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8531 80 90	70	Electro-acoustic transducer	0
ex 8532 29 00	31	Capacitor with two dielectric materials, one in ceramic, the other in epoxy resin, having an initial capacitance of 500 pF ($\pm 35\%$) and a dissipation factor not exceeding 2,5 %	0
ex 8534 00 19	92	Single-face printed circuits fixed on a plastic tape with sprocket holes on both edges, for use in the manufacture of ink jet printer cartridges (a)	0
ex 8536 50 19	91	Hall effect switch, comprising one magnet, one Hall effect sensor and two capacitors, contained in a housing with three connections and bearing: — an identification marking consisting of, or including (one of) the following combination(s): 2AV28E 2AV31E 2AV56 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8536 90 85	93	Contact element with a hold-force of more than 3 N, in the form of two rectangular plastic frames interconnected by electric conductors	0
ex 8540 11 11	93	Colour cathode-ray tube, equipped with one gun with three rays and with a diagonal measurement of the screen of 22 cm or more but not exceeding 26 cm	0
ex 8540 12 00	83	Monochrome cathode-ray tube, with a diagonal measurement of the screen of 150 mm or more but not exceeding 182 mm, a neck diameter of less than 30 mm and an anode voltage of 25 kV or more but not exceeding 32 kV	0
ex 8542 13 01	06	Wafer, not yet cut into chips, consisting only of microcontrollers or microcomputers with a processing capacity of 16 bits, comprising one or more data memories with a total storage capacity not exceeding 16 kbits and one or more programme memories with a total storage capacity not exceeding 512 kbits, for use in the manufacture of goods of subheading 8542 13 65 contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): 7720 77C25 78C12 8XC196KT 77C20 78C11 78C14 or — other identification markings relating to devices complying with the abovementioned description (a)	0
ex 8542 13 13	02	Dynamic random-access memory of C-MOS technology (C-MOS D-RAM), with a storage capacity of 512 K $\times$ 9 bits and an access time not exceeding 80 ns, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): HM514900AJ-8 KM48C512BJ-7 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	TARIC	Description	Rate of autonomous duty (%)																																																								
ex 8542 13 63	09	Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 8 bits, providing communication and control functions in local operating networks (LONs), comprising three 8-bit central processing units (CPUs), in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): MC 143120 MC 143150 or — other identification markings relating to devices complying with the abovementioned description	0																																																								
ex 8542 13 63	18	Microcontroller or microcomputer, with a processing capacity of 8 bits, comprising one or more data memories with a total storage capacity not exceeding 24 kbits and one or more programme memories with a total storage capacity of 32 kbits or more, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): <table style="width: 100%; border: none;"> <tr> <td style="width: 25%;">5A41</td><td style="width: 25%;">87C504</td><td style="width: 25%;">L 39</td><td style="width: 25%;">MN 1871215</td></tr> <tr> <td>5B11</td><td>87C51</td><td>M 37450E8</td><td>P 39</td></tr> <tr> <td>76C75T</td><td>87C52</td><td>M 37450M8</td><td>PCA 84C640</td></tr> <tr> <td>7742</td><td>87C54</td><td>M 38063M6</td><td>PCA 84C840</td></tr> <tr> <td>77C82</td><td>87C58</td><td>M 38063E8</td><td>PCA 84C841</td></tr> <tr> <td>80C152</td><td>87L51</td><td>M 38067M8</td><td>PD 78014</td></tr> <tr> <td>80C51</td><td>Am 79C412</td><td>M 3812</td><td>PD 78058</td></tr> <tr> <td>80C52</td><td>AT 89C51</td><td>M50743</td><td>PD 78064</td></tr> <tr> <td>83C055</td><td>C 1900</td><td>M50747</td><td>PD 78098</td></tr> <tr> <td>83C504</td><td>C 2900</td><td>M50958</td><td>PD 78134</td></tr> <tr> <td>83C51</td><td>C 3900</td><td>M50959</td><td>TMP 87PM70</td></tr> <tr> <td>83L51</td><td>C 40</td><td>MC68HC05i8</td><td>TMP 91P642</td></tr> <tr> <td>8751</td><td>CXD 80724</td><td>MC68HC11A8</td><td></td></tr> <tr> <td>87C055</td><td>CXP 80524</td><td>MC68HC705i8</td><td></td></tr> </table> or — other identification markings relating to devices complying with the abovementioned description	5A41	87C504	L 39	MN 1871215	5B11	87C51	M 37450E8	P 39	76C75T	87C52	M 37450M8	PCA 84C640	7742	87C54	M 38063M6	PCA 84C840	77C82	87C58	M 38063E8	PCA 84C841	80C152	87L51	M 38067M8	PD 78014	80C51	Am 79C412	M 3812	PD 78058	80C52	AT 89C51	M50743	PD 78064	83C055	C 1900	M50747	PD 78098	83C504	C 2900	M50958	PD 78134	83C51	C 3900	M50959	TMP 87PM70	83L51	C 40	MC68HC05i8	TMP 91P642	8751	CXD 80724	MC68HC11A8		87C055	CXP 80524	MC68HC705i8		0
5A41	87C504	L 39	MN 1871215																																																								
5B11	87C51	M 37450E8	P 39																																																								
76C75T	87C52	M 37450M8	PCA 84C640																																																								
7742	87C54	M 38063M6	PCA 84C840																																																								
77C82	87C58	M 38063E8	PCA 84C841																																																								
80C152	87L51	M 38067M8	PD 78014																																																								
80C51	Am 79C412	M 3812	PD 78058																																																								
80C52	AT 89C51	M50743	PD 78064																																																								
83C055	C 1900	M50747	PD 78098																																																								
83C504	C 2900	M50958	PD 78134																																																								
83C51	C 3900	M50959	TMP 87PM70																																																								
83L51	C 40	MC68HC05i8	TMP 91P642																																																								
8751	CXD 80724	MC68HC11A8																																																									
87C055	CXP 80524	MC68HC705i8																																																									
ex 8542 13 65	02	Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising a data memory with a storage capacity of 32 kbits, one or more programme memories with a total storage capacity not exceeding 240 kbits, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): AD 6422 ADSP 2171 ADSP 2178 or — other identification markings relating to devices complying with the abovementioned description	0																																																								
ex 8542 13 67	04	Microcontroller or microcomputer with a processing capacity of 32 bits and a 16-bit data-bus, comprising one or more random-access memories (RAMs) with a total storage capacity not exceeding 450 kbits, one or more read only memories, non-programmable (ROMs) or one or more UV erasable, programmable, read only memories (EPROMs) with a total storage capacity not exceeding 768 kbits, in the form of a monolithic integrated circuit contained in a housing bearing:	-																																																								

CN code	TARIC	Description	Rate of autonomous duty (%)																
ex 8542 13 67 (cont'd)		— an identification marking consisting of, or including (one of) the following combination(s): <table><tr><td>320 10</td><td>320 C 17</td><td>320 C 53</td><td>TMS 320C59</td></tr><tr><td>320 11</td><td>320 C 25</td><td>320 E 15</td><td></td></tr><tr><td>320 C 10</td><td>320 C 50</td><td>320 E 17</td><td></td></tr><tr><td>320 C 15</td><td>320 C 51</td><td>MC68EC000</td><td></td></tr></table> or — other identification markings relating to devices complying with the abovementioned description	320 10	320 C 17	320 C 53	TMS 320C59	320 11	320 C 25	320 E 15		320 C 10	320 C 50	320 E 17		320 C 15	320 C 51	MC68EC000		0
320 10	320 C 17	320 C 53	TMS 320C59																
320 11	320 C 25	320 E 15																	
320 C 10	320 C 50	320 E 17																	
320 C 15	320 C 51	MC68EC000																	
ex 8542 13 67	08	Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 32 bits, comprising a random-access memory (RAM), a time processor unit (TPU) and two serial interface circuits, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): <table><tr><td>MC 68332</td><td>MC 68336</td><td>MC 68F333</td></tr></table> or — other identification markings relating to devices complying with the abovementioned description	MC 68332	MC 68336	MC 68F333	0													
MC 68332	MC 68336	MC 68F333																	
ex 8542 13 91	20	Serial interface circuit, of C-MOS technology, for 4-channel independent full duplex data transfer, with encoding and decoding functions, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): TNETE 2004 or — other identification markings relating to devices complying with the abovementioned description	0																
ex 8542 13 99	58	Transmitter/receiver of C-MOS technology, for the reception and transmission of data at a speed of 98,304 Mbits/s and operating with an internal clock frequency of 49,152 MHz, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): <table><tr><td>TSB 11C01</td><td>TSB 14C01</td></tr></table> or — other identification markings relating to devices complying with the abovementioned description	TSB 11C01	TSB 14C01	0														
TSB 11C01	TSB 14C01																		
ex 8542 14 99 ex 8542 30 95	33 40	Frequency synthesizer, comprising one or more phase-locked loop (PLL) circuits and one or more frequency dividers, with an operating frequency not exceeding 2,8 GHz, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): <table><tr><td>LMX 2331</td><td>M 64074GP</td><td>MC 1 2206</td><td>MC 12310</td></tr><tr><td>LMX 2332</td><td>MC 12179</td><td>MC 12210</td><td>UMA 1015M</td></tr><tr><td>LMX 2335</td><td>MC 12181</td><td>MC 12302</td><td>UMA 1018M</td></tr><tr><td>LMX 2336</td><td>MC 1 2202</td><td>MC 12306</td><td></td></tr></table> or — other identification markings relating to devices complying with the abovementioned description	LMX 2331	M 64074GP	MC 1 2206	MC 12310	LMX 2332	MC 12179	MC 12210	UMA 1015M	LMX 2335	MC 12181	MC 12302	UMA 1018M	LMX 2336	MC 1 2202	MC 12306		0
LMX 2331	M 64074GP	MC 1 2206	MC 12310																
LMX 2332	MC 12179	MC 12210	UMA 1015M																
LMX 2335	MC 12181	MC 12302	UMA 1018M																
LMX 2336	MC 1 2202	MC 12306																	

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8542 19 01	13	Wafer, not yet cut into chips, of gallium arsenide (GaAs) semiconductor material, consisting only of divider/detector circuits, capable of synthesizing frequencies in the range of 50 MHz to 1 700 MHz, comprising a prescaler, a frequency divider and a phase/frequency detector, for use in the manufacture of goods of subheading 8542 19 98 contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): GIGA FSS or — other identification markings relating to devices complying with the abovementioned description (a)	0
ex 8542 19 98	23	12-bit analogue-to-digital converter of BiMOS technology, providing a sampling rate of at least 5 MHz, in the form of a monolithic integrated circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): AD 871 AD 872 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 10	08	Wafer, not yet cut into chips, consisting only of amplifiers, for use in the manufacture of goods of heading or subheading 8471, 8542 30 20, 8542 30 30, 8542 40 50, 8543 89 90 or 9021 40 00 (a)	0
ex 8542 30 20	11	Amplifier, not contained in a housing (chip), for use in the manufacture of goods of heading or subheading 8471, 8542 30 30, 8542 40 50, 8543 89 90 or 9021 40 00 (a)	0
8542 30 30		Amplifiers	0
ex 8542 30 50	01	Voltage regulator, in the form of a monolithic integrated analogue circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): 0 C (RH5 RA 30 AA) LT 1083 MAX 722 16227090 LT 1084 MAX 723 1 B (RH5 RA 21 AA) LT 1085 MAX 732 34 992 LT 1120 MAX 733 CS 8109 (7032FB) LT 1129 MIC 5200 CS 8140 LT 1142 MIC 5201 CS 8141 LT 1149 MIC 5205 EZ 1083 LT 1170 PQ05RH1 EZ 1084 LT 1171 PQ12RH1 EZ 1085 LT 1172 S 8420 EZ 1086 LT 1271 S 8850 LM 1575 LT 1431 SCI 7710Y-KA LM 2575 LT 1510 TK 112 LM 2940 LT 1511 TK 113 LP 2950 LT 1512 TK 11430M LP 2951 LT 1585 TK 11440M LP 2980 MIC 2951 TK 114 (R3) LT 1020 MAX 717 TK 115 LT 1070 MAX 718 TK 116 LT 1071 MAX 719 TK 71350M LT 1074 MAX 720 TL750M LT 1076 MAX 721 TL751M	

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8542 30 50 (cont'd)		or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 65	03	Speedometer and odometer drive and control circuit, whether or not having amplification functions, comprising frequency dividers, in the form of a monolithic integrated mixed analogue–digital circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): TA 8906 TB 9208 TB 9230 TB 9258N TB 9207 TB 9212 TB 9250N or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 69	19	4–channel control circuit, of bipolar technology, capable of driving the motor and the optical unit of a compact disc player, comprising amplifiers and a thermal protection circuit, in the form of a monolithic integrated analogue circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): BA 5941FP BA 6297AFP BA 6392FP or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 95	09	Encoder/decoder with pulse–code–modulation filter, comprising an analogue–to–digital converter and a digital–to–analogue converter, in the form of a monolithic integrated mixed analogue–digital circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): MC 145480 MC 145483 MT 896 MC 145481 MC 145503 TMC 129C18 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 95	47	9–bit analogue–to–digital converter of BiMOS technology, in the form of a monolithic integrated mixed analogue–digital circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): AD 9049 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 95	48	Demodulator, capable of identifying a telephone–line calling–number, in the form of a monolithic integrated mixed analogue–digital circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): MC 145447 MT 8841 MT 8843 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8542 30 95	49	Demodulator, comprising a clock synchronization circuit, filters, phase-locked loop (PLL) circuits and decoders, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): BU 1921 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 95	50	6-bit digital-to-analogue converter, comprising a serial interface circuit, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): MC 144110 MC 144111 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 95 ex 8542 30 99	51 72	Graphic display equalizer circuit, comprising seven passband filters, in the form of a monolithic integrated mixed analogue-digital or analogue circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): BA 3834 XR 1090 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 99	29	Voltage reference circuit, in the form of a monolithic integrated analogue circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): AD 580 AD 680 LM 4040 LT 1004 LT 1021 REF 102 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 99	63	Voltage comparator, operating within a common voltage range of -12 V or more but not exceeding +36 V and a differential voltage range of -24 V or more but not exceeding +24 V and a response time not exceeding 2,5 µs, in the form of a monolithic integrated analogue circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): EL 2019 LM 219 LM 319 TS 3702 LM 119 LM 2921 LT 1016 TS 393 or — other identification markings relating to devices complying with the abovementioned description	0

CN code	TARIC	Description	Rate of autonomous duty (%)
ex 8542 30 99	74	Audio signal processing circuit, providing frequency equalizer and mute functions, in the form of a monolithic integrated analogue circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): HA 1218NT or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 30 99	75	Video and audio recording and reproducing signal processing circuit, providing audio gain stabilization and audio equalization control, in the form of a monolithic integrated analogue circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): LA 71520 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 40 10	03	Microprocessor, only consisting of: — not more than four central processing units (CPUs), — not more than two cache memories, and — capacitors, in the form of a hybrid integrated circuit contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): 40H9500 40H9502 or — other identification markings relating to devices complying with the abovementioned description	0
ex 8542 40 10 ex 8542 40 90	04 10	Hybrid integrated circuit, consisting only of a monolithic integrated circuit and decoupling capacitors, contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): 11H4863 26H3566 26H6718 63F4582 98F2625 21H4867 26H45 63F3630 63G4582 98F2775 or — other identification markings relating to devices complying with the abovementioned description	0
8542 40 50	04	Amplifiers	0
ex 8542 50 00	04	Silicon diode assembly comprising: — a diode with a peak reverse voltage of 600 V or more and a reverse recovery time not exceeding 0,4 µs, and — a diode with a peak reverse voltage of 1 500 V or more and a reverse recovery time not exceeding 1,5 µs, each diode having the same polarity, in the form of a microassembly contained in a housing	0

CN code	TARIC	Description	Rate of autonomous duty (%)																																												
ex 8542 50 00	09	Quintuple field-effect transistor (FET), having a drain-to-source breakdown-voltage of 150 V or more, operating with a continuous drain current not exceeding 7 A, and with a dissipation rate not exceeding 35 W, in the form of a microassembly contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): SLA 5038 or — other identification markings relating to devices complying with the abovementioned description	0																																												
ex 8543 89 90	62	Amplifier, consisting of active and passive elements mounted on a printed circuit, contained in a housing bearing: — an identification marking consisting of, or including (one of) the following combination(s): <table border="0"> <tr> <td>FA 01314</td><td>MHW 704</td><td>MHW 926</td><td>PHW 902</td></tr> <tr> <td>FA 01317</td><td>MHW 707</td><td>MHW 927</td><td>PHW 925</td></tr> <tr> <td>FA 01321</td><td>MHW 720</td><td>MHW 953</td><td>SHW 5115</td></tr> <tr> <td>FMC 1717</td><td>MHW 803</td><td>PF 0144</td><td>XHW 105</td></tr> <tr> <td>FMC 1819</td><td>MHW 820-1</td><td>PF 0146</td><td>XHW 2803</td></tr> <tr> <td>ISO 122</td><td>MHW 820-2</td><td>PF 0148</td><td>XHW 2902</td></tr> <tr> <td>MHW 105</td><td>MHW 9002</td><td>PF 0412</td><td>XHW 5115</td></tr> <tr> <td>MHW 1815</td><td>MHW 910</td><td>PHW 2905</td><td>XHW 903</td></tr> <tr> <td>MHW 2701</td><td>MHW 914</td><td>PHW 2907</td><td></td></tr> <tr> <td>MHW 2707</td><td>MHW 915</td><td>PHW 5113</td><td></td></tr> <tr> <td>MHW 607</td><td>MHW 916</td><td>PHW 9012</td><td></td></tr> </table> or — other identification markings relating to devices complying with the abovementioned description	FA 01314	MHW 704	MHW 926	PHW 902	FA 01317	MHW 707	MHW 927	PHW 925	FA 01321	MHW 720	MHW 953	SHW 5115	FMC 1717	MHW 803	PF 0144	XHW 105	FMC 1819	MHW 820-1	PF 0146	XHW 2803	ISO 122	MHW 820-2	PF 0148	XHW 2902	MHW 105	MHW 9002	PF 0412	XHW 5115	MHW 1815	MHW 910	PHW 2905	XHW 903	MHW 2701	MHW 914	PHW 2907		MHW 2707	MHW 915	PHW 5113		MHW 607	MHW 916	PHW 9012		0
FA 01314	MHW 704	MHW 926	PHW 902																																												
FA 01317	MHW 707	MHW 927	PHW 925																																												
FA 01321	MHW 720	MHW 953	SHW 5115																																												
FMC 1717	MHW 803	PF 0144	XHW 105																																												
FMC 1819	MHW 820-1	PF 0146	XHW 2803																																												
ISO 122	MHW 820-2	PF 0148	XHW 2902																																												
MHW 105	MHW 9002	PF 0412	XHW 5115																																												
MHW 1815	MHW 910	PHW 2905	XHW 903																																												
MHW 2701	MHW 914	PHW 2907																																													
MHW 2707	MHW 915	PHW 5113																																													
MHW 607	MHW 916	PHW 9012																																													
ex 9001 90 90	50	Rear projection screen, comprising a lenticular plastic plate, for use in the manufacture of products falling within heading 8528 (a)	0																																												
ex 9006 91 00 ex 9006 99 00	10 10	Parts, for use in the manufacture of products falling within subheading 9006 40 00 (a)	0																																												
ex 9013 80 90	10	Polarization insensitive fibre-optic isolator, operating at a wavelength of 1 200 nm or more, contained in a cylindrical housing	0																																												
ex 9013 90 90	10	Rod of neodymium-doped yttrium-aluminium garnet (YAG) material, polished at both ends	0																																												
ex 9031 80 39	10	Acceleration measurement device for automotive airbags, comprising one or more active and/or passive elements and a sensor, the whole contained in a housing	0																																												
ex 9608 91 00	20	Felt tips and other porous-tips for markers, without internal canal	0																																												

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

ANEXO II — BILAG II — ANHANG II — ΠΑΡΑΡΤΗΜΑ II — ANNEX II — ANNEXE II — ALLEGATO II —
BIJLAGE II — ANEXO II — LIITE II — BILAGA II

Código NC KN-kode KN-Code Κωδικός ΣΟ CN code Code NC Codice NC GN-code Código NC CN-koodi KN-nummer	Taric	Código NC KN-kode KN-Code Κωδικός ΣΟ CN code Code NC Codice NC GN-code Código NC CN-koodi KN-nummer	Taric	Código NC KN-kode KN-Code Κωδικός ΣΟ CN code Code NC Codice NC GN-code Código NC CN-koodi KN-nummer	Taric
ex 2914 70 90	20	ex 8542 13 13	04	ex 8542 30 50	12
ex 2918 19 10	10	ex 8542 13 63	09	ex 8542 30 50	13
ex 2923 90 00	10	ex 8542 13 63	18	ex 8542 30 50	14
ex 2926 90 80	20	ex 8542 13 65	02	ex 8542 30 50	15
ex 3815 19 90	30	ex 8542 13 67	04	ex 8542 30 50	16
ex 3904 40 00	91	ex 8542 13 67	08	ex 8542 30 50	17
ex 3921 19 90	91	ex 8542 19 05	08	ex 8542 30 50	18
ex 5504 90 00	10	ex 8542 30 10	01	ex 8542 30 50	19
ex 7006 00 90	30	ex 8542 30 10	03	ex 8542 30 50	20
ex 7011 20 00	40	ex 8542 30 10	04	ex 8542 30 50	21
ex 7011 20 00	50	ex 8542 30 10	05	ex 8542 30 50	22
ex 8101 99 00	10	ex 8542 30 10	06	ex 8542 30 50	23
ex 8108 90 90	92	ex 8542 30 20	01	ex 8542 30 50	24
ex 8471 70 51	30	ex 8542 30 20	02	ex 8542 30 65	03
ex 8473 30 10	80	ex 8542 30 20	07	ex 8542 30 95	04
ex 8473 40 90	85	ex 8542 30 30	01	ex 8542 30 95	09
ex 8504 40 99	10	ex 8542 30 30	02	ex 8542 30 95	10
ex 8507 30 91	20	ex 8542 30 30	03	ex 8542 30 95	40
ex 8507 80 91	10	ex 8542 30 30	04	ex 8542 30 99	28
ex 8507 80 99	10	ex 8542 30 30	05	ex 8542 30 99	29
ex 8517 90 88	20	ex 8542 30 30	06	ex 8542 30 99	63
ex 8521 90 00	91	ex 8542 30 30	07	ex 8542 30 99	72
ex 8531 80 90	20	ex 8542 30 30	08	ex 8542 40 50	01
ex 8532 25 00	31	ex 8542 30 30	09	ex 8542 40 50	02
ex 8532 29 00	31	ex 8542 30 30	10	ex 8542 40 50	03
ex 8541 10 91	40	ex 8542 30 30	11	ex 8542 40 50	04
ex 8542 13 01	02	ex 8542 30 30	12	ex 8542 40 50	05
ex 8542 13 01	03	ex 8542 30 30	13	ex 8542 40 50	07
ex 8542 13 01	06	ex 8542 30 30	14	ex 8542 40 50	08
		ex 8542 30 30	15	ex 8542 40 50	09
		ex 8542 30 30	16	ex 8542 40 50	10
		ex 8542 30 30	17	ex 8542 40 50	11
		ex 8542 30 30	18	ex 8542 50 00	04
		ex 8542 30 30	19		
		ex 8542 30 30	20	ex 8543 89 90	31
		ex 8542 30 30	21	ex 8543 89 90	32
		ex 8542 30 30	23	ex 8543 89 90	33
		ex 8542 30 30	24	ex 8543 89 90	34
		ex 8542 30 30	25	ex 8543 89 90	35
		ex 8542 30 30	28	ex 8543 89 90	39
		ex 8542 30 50	01	ex 8543 89 90	49
		ex 8542 30 50	02	ex 8543 89 90	57
		ex 8542 30 50	03	ex 8543 89 90	60
		ex 8542 30 50	04		
		ex 8542 30 50	05	ex 8548 90 00	35
		ex 8542 30 50	06	ex 8548 90 00	38
		ex 8542 30 50	07		
		ex 8542 30 50	08		
		ex 8542 30 50	09	ex 9013 80 90	10
		ex 8542 30 50	10		
		ex 8542 30 50	11	ex 9031 80 39	10